DAIMLERCHRYSLER

Vehicle IT and Services Research Berlin - Stuttgart - Ulm - Palo Alto driving connectivity

2007 ITS World Congress, London, U.K. SS 59 – Communications for Vehicle Safety Vehicle Safety Communications in the US

Dr. Wieland Holfelder, VP&CTO DaimlerChrysler Research and Technology North America, Inc.

October 11, 2006



International V2I and V2V Support

U.S., Europe and Japan all show significant activities in the area of Vehicle to Infrastructure and Vehicle to Vehicle Communications (though with somewhat different starting positions and different focus):

RF bands		20 Mills at 5.0 Cills allocation			
	Focus of today's presentation	likely by 2010	20 MHz at 5.8 GHz allocated since 1997		
Political Environment		Strong political support by the European Union and most National Governments	ETC infrastructure in place Rollout of infrastructure for vehicle safety communications ongoing		
Activities		Sichere Intelligente Mobilität Testfeld Deutschland (SIM TD) COM eSafety Car2Car-Communications Consortium (C2C-CC) CVIC, SAFESPOT	Smartway (i.e. Vehicle Communications Infrastructure for Safety and Mobility) ASV-4 (i.e. Vehicle to Vehicle Communications for Safety)		



·5:3:





:53:						D	AIMLERCH	IRYSLER
Basic Com High-Priori	munica ity App	ations I licatior	Require n Scenai	ments f rios	or	•	VSC	
	Traffic Signal Violation Warning	Curve Speed Warning	s TSS	Pre-Crash Warning	Cooperative Forward Collision Warning	Left Turn Assistant	Lane Change Warning	Stop Sign Movement Assistance
Types of Communication	one-way, point- multipoint	one-way, point- multipoint	electer or san	two-way, point- point	one-way, point- multipoint	one-way, point- multipoint	one-way, point- multipoint	one-way, point- multipoint
Transmission Mode	periodic	periodic	d by	event- driven	periodic	periodic	periodic	periodic
Minimum Frequency (Hz)	10	1	the	50	10	10	10	10
Allowable Latency (milliseconds)	100	1000	CAMF	20	100	100	100	100
Estimated Message Size (bytes)	500	200	• OE	200	200	500	200	500
Maximum Required Range of Communication (meters)	250	200	on IMs	50	150	300	150	300
		n between	Infrastructur	e & vehicle	es Requ	ires commu	nication bet	ween vehic























·5:5; DAIMLERCHRYSLER **VII POC Applications** VII Safety In-Vehicle Signage • Extended Emergency Brake Light Work zone warning Traffic Signal Violation Warning School zone warning Speed limit **Present Traffic Information** Icy bridge ahead Off-board navigation Icy road Dynamic traffic information · Clearance height Optimized routing Wrong way Incident information · Curve ahead Estimated travel times Next exit services Weather information **Make Payments** Toll road Gasoline purchases Parking fees

Dr. W. Holfelder DaimlerChrysler RTNA, Inc.

October 11th, 2006

19









·C-7·	DAIMLERCHRYSLER
Thank You!	
Dr. Wieland Holfelder DaimlerChrysler Research and Technology North Ameri Vice President & CTO	ica, Inc.
1510 Page Mill Road Palo Alto, CA 94304 USA	
Phone: +1-650-845-2568/2518 Fax: +1-650-845-2555 E-Mail: Wieland.Holfelder@DaimlerChrysler.com	
Dr. W. Holfelder DaimlerChrysler RTNA, Inc. October 11th, 2006	24



